





Multi-protocol Radio HDL460A

Hi-Target radio modems provide reliable data communications for mission-critical applications where a combination of stability, supreme performance and long range are required. The HDL460A radio is the latest multi-protocol radio station of Hi-Target. Its adjustable multiple transmit power can easily achieve stable transmission over long distances of 20 kilometers.

KEY FEATURES

- HD OLED display.
- Real-time voltage detection.
- Compatible with major radio protocols in the industry.

| General Specification | | |
|-----------------------------------|-----------------------------|---------------------|
| Frequency range | 403~473MHz | |
| Operating mode | Half-duplex | |
| Channel spacing | 25KHz, 12.5KHz | |
| Modulation type | 4FSK, GMSK | |
| Operation voltage | 12V | |
| Power Dissipation (Typical) | High power level (35W) | ≤87.5 W @ DC 12V |
| | Low power level (10W) | ≤52W @ DC 12V |
| Size | 178 mm * 128.5 mm * 76.9 mm | |
| Weight | 1.495 Kg | |
| Temperature(operation) | -30°C~+65°C | |
| Temperature (storage) | -50°C~+80°C | |
| Antenna Port | UHF, TNC | |
| Data Interface | LEMO 5Pin | |
| Rf Output Power | 50dBc (10 W) | |

- The longest communication distance with the comparison products in the industry.
- The adaptive frequency can adapt the default frequency of different manufactures 10 W, 35 W power can be set up.
- Industrial-Grade processing platform.

| Modem | |
|-----------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protocol | HI-TARGET9600, HI-TARGET19200, TRIMTALK450S, TRIMMARK III, SOUTH9600, SOUTH19200, CHC9600, CHC19200, TRANSEOT, SATEL-3AS 25K, SATEL-3AS 12.5K |
| Channel Number | 116 |
| Air Baud Rate | 9600 bps, 19200 bps |
| Modulation Type | GMSK |
| Serial Port Baud Rate | 9600 bps, 19200 bps, 38400 bps, 57600 bps, 115200 bps |
| User Interface | |
| User Interfa | |
| User Interfa Display | 1.3 inch (screen), 128 * 64 resolution |
| | |
| Display | 1.3 inch (screen), 128 * 64 resolution |
| Display Button | 1.3 inch (screen), 128 * 64 resolution5 buttons1 power light, 1 blinker |
| Display Button Indicator | 1.3 inch (screen), 128 * 64 resolution5 buttons1 power light, 1 blinker |
| Display Button Indicator Environme | 1.3 inch (screen), 128 * 64 resolution 5 buttons 1 power light, 1 blinker |
| Display Button Indicator Environme Waterproof | 1.3 inch (screen), 128 * 64 resolution 5 buttons 1 power light, 1 blinker ntal IP67 |

20A204



AUTHORIZED DISTRIBUTION PARTNER

Hi-Target Surveying Instrument Co. Ltd

ADD: Building 13, Tian'An Technology Zone HQ Center, No. 555, North of Panyu RD, Panyu District, 511400 Guangzhou, China. www.hi-target.com.cn +86-20-28688296 info@hi-target.com.cn